



CIRCLE REVERSE OSMOSIS SYSTEM











KEY FEATURES

Water Saving Technology – Patented technology eliminates backpressure common in conventional RO systems making the Circle up to 10 times more efficient than existing products.

Saves You Money – Conventional RO systems waste up to 24 gallons of water per every 1 gallon of filtered water produced. The Circle only wastes an average of 2.4 gallons of water per 1 gallon of filtered water produced, saving you water and money over the life of the product!.

RO Filter Auto Flushing – Significantly extends life of RO filter.

Chrome Faucet Included – With integrated LED filter change indicator.

Space Saving Compact Design – Integrated rapid refill tank means more space under the sink.



The RC100 conforms to NSF/ANSI 42, 53 and 58 for the reduction of Aesthetic Chlorine, Taste and Odor, Cyst, VOCs,

Fluoride, Pentavalent Arsenic, Barium, Radium 226/228, Cadmium, Hexavalent Chromium, Trivalent Chromium, Lead, Copper, Selenium and TDS as verified and substantiated by test data. The RC100 conforms to NSF/ANSI 372 for low lead compliance.

SPECIFICATIONS

| Product Name | H2O+ Circle Reverse Osmosis Water Filtration System |
|----------------------------|---|
| Model / SKU | RC100 |
| Installation | Undercounter |
| Filters & Lifespan | Sediment Filter, Pre-Carbon Plus Filter, Post Carbon Block Filter (RF-20): 6 months RO Membrane Filter (RF-40): 24 months |
| Tank Capacity | 6 Liters (refills fully in less than one hour) |
| Dimensions | 9.25" (W) × 16.5" (H) × 13.75" (D) |
| Net weight | 14.6 lbs |
| Min/Max Operating Pressure | 40 psi – 120 psi (275Kpa – 827Kpa) |
| Min/Max Water Feed Temp | 41° F – 95° F (5° C – 35° C) |
| Faucet Flow Rate | 0.26 – 0.37 gallons per minute (gpm) at incoming water pressure of 20–100 psi |
| Rated Service Flow | 0.07 gallons per minute (gpm) |
| Warranty | One Year Warranty |

Sprondell