# SWASH CL1500

# ADVANCED BIDET SEAT





CL1500-EW / CL1500-RW

Elongated White / Round White

Swash CL1500 provides optimal comfort and a superior clean with all the features you'd expect from an advanced bidet seat. Comes with all parts for a standard installation, including a  $\frac{7}{8}$  metal T-valve and metal braided bidet hose.

# **TECHNICAL SPECIFICATIONS**

Model/SKU	CL1500-EW, CL1500-RW
Power Voltage	120V / 60Hz
Max Power Consumption	870W
Supply Water Pressure	9.95 psi – 106.7 psi
Dimensions	<b>Elongated:</b> 18.5 in x 20.7 in x 5.7 in / <b>Round:</b> 15.9 in x 19.5 in x 5.7 in
Power Cord Length	3.9 ft
CL1500-EW Weight	Elongated: 11.46 lbs / Round: 11.0 lbs
CL1500-RW Weight	Elongated: 11.9 lbs / Round: 11.46 lbs
Incoming Water Temperature	37.4°F – 104°F
Seat Weight Limit	330 lbs
Lid Weight Limit	160 lbs
Seat Opening Dimensions	<b>Elongated:</b> 11.9 in x 8.1 in / <b>Round:</b> 10.6 in x 8.1 in
Mesh Filter	0.51 in x 0.44 in diameter





# SWASH CL1500

### ADVANCED BIDET SEAT



## **HEATED SEAT SPECIFICATIONS**

Seat Temperature Control	<b>4 levels:</b> Off – room temperature, Low – 93.2°F, Medium – 100.4°F, High – 107.6°F
Heater Power Consumption	55W
Safety Devices	Thermostat, Thermal Fuse, Thermal Sensor, Seat Occupied Sensor

#### WARM WATER WASHING DEVICE

Rear Wash	Maximum 0.8 L/min., automatic nozzle self-cleaning
Front Wash	Maximum 0.8 L/min., automatic nozzle self-cleaning
Strong Wash	Maximum 0.6 L/min., automatic nozzle self-cleaning
Standard Time	Rear Wash: 2 minutes / Front Wash: 2 minutes / Strong Wash: 2 minutes
Water Pressure Control	5 levels
Water Temperature Control	4 levels: Off – incoming water temp., Low – 91.4°F, Medium – 96.8°F, High – 102.2°F
Heater Power Consumption	800W
Safety Devices	Thermal Fuse, Thermostat, Water Level Sensor, Thermal Sensor, Bi-metal

#### **HYGIENE**

- Rear, Front, and Strong wash
- Stainless-steel nozzle
- Positionable nozzle
- Adjustable water pressure
- Adjustable water temperature
- Nozzle oscillation

### **COMFORT**

- Gentle Wash function
- Ergonomic heated seat with adjustable temperature
- Massage and pulse
- Warm air dryer
- Automatic carbon deodorizer
- Continuous heated water

#### **CONVENIENCE**

- Illuminating nightlight
- Dual Eco Mode for energy savings
- Sidearm control panel
- Gentle-closing seat and lid
- Quick release seat

#### **REQUIRED MEASUREMENTS**

A. Center of bolt holes to front of toilet bowl

Elongated Swash models: 18"—19.5" Round Swash models: 16"—17.75"

**B.** Distance from center of bolt holes to toilet seat tank All models: Minimum 1.5"

All models. Willimum 1.5

C. Distance between bolt holes All models: 5.25"—7.45"



